



intAct Premium-Power

Maintenance-free calcium battery (Ca/Ca) | wet charged



intAct Premium-Power

30% extra starting power

This car battery is ideally suited for highly equipped vehicles with many electrical consumers and in intensive urban traffic. With minimal self-discharge, particularly safe and temperature-resistant.

Our recommendation for vehicles with a lot of equipment, especially if you often drive short distances.

CHARACTERISTICS

- » **30% more starting power** than standard starter batteries with the same box size.
- » **Fast charging. Up to 1.5 times shorter charging time** due to faster current consumption than standard starter batteries of the same box size.
- » **Double lid for increased leakage protection and vapour condensation** (gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).
- » Approved for **charging voltage up to 14.8 volts.**
- » **Filled and charged.**
Maintenance-free. Ready to use.

All information about this series can be found on the Internet:

VISIT US!



www.intact-batterien.de 🔍

intAct Premium Power

Maintenance-free calcium battery (Ca/Ca) | wet charged

Item Nr.	Short Code	Volt	Capacity	Cold cranking amper	Length mm	Width mm	Height mm	Position of Terminal	Terminal	Base plate	Degasing	Weight/ kg
PP45MF	–	12	45 Ah (c20)	450 A (EN)	207	175	175	0	1	B13	–	12,1
PP50MF	–	12	50 Ah (c20)	540 A (EN)	207	175	190	0	1	B13	–	12,8
PP60MF	–	12	60 Ah (c20)	600 A (EN)	242	175	175	0	1	B13	–	13,8
PP65MF	–	12	65 Ah (c20)	640 A (EN)	242	175	190	0	1	B13	–	14,9
PP75MF	–	12	75 Ah (c20)	720 A (EN)	278	175	175	0	1	B13	–	16,8
PP78MF	–	12	78 Ah (c20)	760 A (EN)	278	175	190	0	1	B13	–	17,6
PP85MF	–	12	85 Ah (c20)	800 A (EN)	315	175	175	0	1	B13	–	18,9
PP90MF	–	12	90 Ah (c20)	720 A (EN)	315	175	190	0	1	B13	–	19,3
PP100MF	–	12	100 Ah (c20)	900 A (EN)	353	175	190	0	1	B13	–	22,1
intAct Premium-Power Asia												
PP38MF-ASIA	–	12	40 Ah (c20)	350 A (EN)	187	127	227	0	3	B01	–	9,1
PP45MF-ASIA	–	12	45 Ah (c20)	390 A (EN)	237	127	225	0	3	B01	–	11,5
PP65MF-ASIA	–	12	65 Ah (c20)	580 A (EN)	230	172	220	0	1	B01	–	16,1
PP75MF-0-ASIA	–	12	75 Ah (c20)	630 A (EN)	270	173	222	0	1	B01	–	17,6
PP75MF-1-ASIA	–	12	75 Ah (c20)	630 A (EN)	270	173	222	1	1	B01	–	17,6
PP95MF-0-ASIA	–	12	95 Ah (c20)	800 A (EN)	304	173	220	0	1	B01	–	21
PP95MF-1-ASIA	–	12	95 Ah (c20)	800 A (EN)	304	173	220	1	1	B01	–	21

