



- Battery charger and maintainer with TRONIC technology for 12/24V lead batteries for motorbikes, cars, vans, etc.
- Automatic charge and maintenance in Tronic at 12/24V. 12V starting.
- Advanced charge and maintenance functions for EFB, AGM and low temperature.
- Digital display for voltage, current and charge percentage. Warning LED to indicate battery charge status and end of charge;
- Protection against overloads and polarity reversal.

TECHNICAL DATA

CODE	807579	CHARGE AND STARTING VOLTAG.	12 / 24 V	MIN.RATED REFERENCE CAPAC.	10 / 10 Ah
SINGLEPHASE MAINS VOLTAGE	230 V	EFFECTIVE CHARGING CURRENT	25 / 12 A	MAX.RATED REFERENCE CAPAC.	300 / 160 Ah
MAINS FREQUENCY	50 / 60 Hz	RATED CHAR.CUR.EN60335-2-29	15 / 8 A	ADJUSTMENT POSITIONS	5
CHARGING ABSORBED POWER	300 W	START CUR.1V/C EN60335-2-29	100 A	DIMENSIONS (LxWxH)	24,5 x 19,5 x13 cm
STARTING ABSORBED POWER	2,2 kW	MAX STARTING CURRENT	150 A	WEIGHT	7,57 kg

DESCRIPTION

Electronic battery charger and maintainer with TRONIC technology for WET, GEL, AGM, MF, PbCa, EFB batteries at 12V/24V.

12V starter.

Advanced charging and maintenance functions for EFB, AGM and low temperature batteries.

Display for voltage, current, and charge percentage.

Features:

- Automatic charge and maintenance in Tronic at 12/24V;
- 12V starting;
- Advanced charging and maintenance functions for EFB, AGM and low temperature ;
- Digital display for voltage, current and charge percentage ;
- Warning LED to indicate battery charge status and end of charge;
- Protection against overloads and polarity reversal.

Complete with cable with clamps.

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



CERTIFICATE