



intAct Traktion-Power

Closed lead-acid battery with reinforced grid plates | low maintenance

Art.No.

95950GUG

Volt	12V
Capacity	95 Ah (c5)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	330 x 172 x 242 mm
Weight	25 kg
Pos. of Terminal	1
Terminal	1
Bodenleiste	-



Usage




Proven and cost-conscious


Due to their excellent high-current characteristics, they are particularly suitable for propelling golf carts, small leisure vehicles, wheelchairs, mobile lifting platforms, cleaning machines and forklifts. Our recommendation, for all who are looking for an inexpensive traction battery and are not afraid of maintenance.

- » Filled and charged. Ready for immediate use.
- » Light cyclic use: 300 cycles according to IEC 254-1.
- » Reinforced special-insulation grid plates with high mass utilisation for maximum capacity reserves.
- » 6-volt and 12-volt versions.
- » Optional water filling system can be attached to extend service intervals.
- » Flooded lead-acid battery. Low maintenance.


Size



Pos. of Terminal 1



Terminal 1



Bodenleiste -

As of 13.05.2026