


Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	2.1AH	
Dimensions	Length	178±2mm (7.00 inches)
	Width	35±1mm (1.38 inches)
	Container Height	60±1mm (2.36 inches)
	Total Height (with Terminal)	66±1mm (2.60 inches)
Approx Weight	Approx 0.96 kg (2.12lbs)	
Terminal	T1	
Container Material	ABS	
Rated Capacity	2.10 AH/0.105A	(20hr ,1.80V/cell,25°C/77°F)
	1.95AH/0.195A	(10hr,1.80V/cell,25°C/77°F)
	1.78 AH/0.357A	(5hr,1.75V/cell,25°C/77°F)
	1.61 AH/0.536A	(3hr,1.75V/cell,25°C/77°F)
	1.32 AH/1.32A	(1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	31.5A (5s)	
Internal Resistance	Approx 90mΩ	
Operating Temp.Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 0.63A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40° C (104° F)	103%
	25° C (77° F)	100%
	0° C (32° F)	86%
Self Discharge	General purpose batteries may be stored for up to 6 months at 25° C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	
Life expectancy	3~5 years at 25° C with charge voltage of 2.25V/cell	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Conform to:
IEC60896-21&22 and/or IEC61427

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	4.00	3.07	2.54	2.20	1.70	1.25	1.06	0.625	0.489	0.397	0.324	0.281	0.227	0.189	0.104
1.80V/cell	5.37	3.92	3.07	2.60	2.01	1.46	1.18	0.682	0.526	0.424	0.348	0.302	0.240	0.195	0.105
1.75V/cell	6.05	4.31	3.36	2.80	2.08	1.51	1.24	0.707	0.536	0.434	0.357	0.310	0.245	0.201	0.106
1.70V/cell	6.66	4.70	3.58	2.94	2.17	1.57	1.28	0.725	0.550	0.445	0.366	0.316	0.248	0.205	0.108
1.65V/cell	7.35	5.07	3.81	3.12	2.29	1.61	1.31	0.735	0.574	0.461	0.376	0.323	0.252	0.209	0.109
1.60V/cell	8.11	5.51	4.08	3.33	2.42	1.68	1.32	0.767	0.591	0.475	0.389	0.330	0.254	0.211	0.110


Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	7.31	5.67	4.75	4.15	3.24	2.41	2.04	1.21	0.95	0.777	0.635	0.553	0.448	0.375	0.206
1.80V/cell	9.71	7.16	5.66	4.83	3.77	2.78	2.27	1.31	1.02	0.825	0.679	0.590	0.473	0.386	0.208
1.75V/cell	10.7	7.75	6.10	5.15	3.88	2.86	2.36	1.36	1.03	0.840	0.694	0.605	0.480	0.396	0.210
1.70V/cell	11.5	8.25	6.43	5.37	4.01	2.96	2.43	1.39	1.06	0.861	0.711	0.616	0.487	0.403	0.213
1.65V/cell	12.5	8.82	6.78	5.66	4.20	3.01	2.47	1.40	1.10	0.887	0.728	0.628	0.493	0.411	0.216
1.60V/cell	13.4	9.36	7.13	5.96	4.40	3.12	2.48	1.45	1.13	0.913	0.749	0.639	0.497	0.415	0.217


Dimensions

T1 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics

