



**intAct GEL-Power - Marine & Leisure**

Sealed GEL battery with grid plates | electrolyte gel-bonded | filled and charged | absolutely maintenance-free

Art.No.

# GEL-300-06

<b>Volt</b>	6V
<b>Capacity</b>	240 Ah (c5), 300 Ah (c20), 330 Ah (c100)
<b>CCR -18°C (EN)</b>	-
<b>Electrolyte</b>	diluted sulphuric acid
<b>Electrolyte density</b>	1,28 +/- 0,01 Kg/l (25° C)
<b>Size (LxWxH)</b>	312 x 180 x 359 mm
<b>Weight</b>	48 kg
<b>Pos. of Terminal</b>	1
<b>Terminal</b>	1
<b>Base plate</b>	-

**Usage**




## Strong and maintenance-free

Perfect for professional storage and supply needs associated with renewable energy systems, coaches, campers or boats. Withstands charging-current fluctuations, relative deep discharges and continuous recharging. Our recommendation for anyone looking for a more cycle-resistant, spill-proof supply battery.


- » **For medium to heavy cyclic use.** 400 - 700 cycles according to IEC 254-1.
- » **Longer service life than flooded lead-acid battery.**
- » **High vibration resistance.**
- » **Low self-discharge.**
- » **In 6-volt and 12-volt versions.**
- » **Sealed GEL battery** with grid plates.
- » **VRLA battery with gas recombination and safety valves,** where refilling is neither possible or necessary.




Size



Pos. of Terminal 1



Terminal 1



Base plate -

As of 04.09.2025