



intact Start-Power Truck

Closed calcium or hybrid battery (Ca/Ca or Sb/Ca) | low/maintenance-free

Art.No.

60035GUG

Volt	12V
Capacity	100 Ah (c20)
CCR -18°C (EN)	600 A (EN)
Electrolyte	verdünnte Schwefelsäure +++ diluted sulfuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25°C)
Size (LxWxH)	413 x 175 x 215 mm
Weight	27,5 kg
Pos. of Terminal	1
Terminal	1
Base plate	-

Usage




Top performance at a good price

Developed for performance and extreme high-current capability at an absolutely perfect price-performance ratio. For almost all standard trucks without many additional installations and other electrical consumers. Our recommendation for standard applications with low requirements and the best price-performance ratio.


- » **Powerful and reliable.**
- » **Double lid for increased leakage protection and gas condensation** (gaseous electrolyte condenses in the labyrinth lid and remains in the circuit).
- » **Maintenance-free. No refilling of water necessary.**
- » **Filled and charged (GUG), ready for immediate use.**
- » Available for **trucks as a conventional wet starter battery**, as well as **super heavy duty (SHD)** with glass fiber fleece separators **vibration-resistant V3**.
- » **30% more cycles** compared to conventional commercial vehicle batteries.



Size



Pos. of Terminal 1



Terminal 1



Base plate -

As of 02.09.2025