




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

</ul

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%

depth of discharge cycles EverSys World Headquarters



Enersys EMEA EH Europe GmbH 2366 Bernville Road Baarerstrasse 18 Reading, PA 19605, USA 6300 Zug, Switzerland Tel: +1-800-964-2837

Building

EnerSys Asia 152 Beach Road #11-08 Gateway East Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library





ODP-AGM25

website for updates.

(25-PC1400)

12:37:07

Battery Type

- Group 25 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

PDF Generated at https://eu.odysseybattery.com 02/16/2023

Information correct at time of exporting PDF. Please check

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1200A
Cold Cranking Amps (CCA)	765A
НСА	900A
MCA	770A
20Hr Nominal Capacity (Ah)	59Ah
10Hr Nominal Capacity (Ah)	55Ah
Reserve Capacity Minutes	117 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	N/A
Internal Resistance (mΩ)	4.3 mΩ
Short Circuit (A)	1850A

Dimensions and Weight

Length	9.5 in / 241 mm
Width	6.9 in / 175 mm
Height (terminals included)	8.8 in / 224 mm
Height (container)	8.1 in / 206 mm
Weight	50.0 lbs / 22.7 kg

Temperature

Operating temperature range	-40°F/-40°C to 140°F/+60°C
Optimum storage temperature	68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

© 2023 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: February 16, 2023

www.odvssevbatterv.com www.enersvs.com