





Drawings & Terminal Position



ODP-AGM35 RIGHT POSITIVE SAE TERMINALS





Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve IUU Charger voltage at 68°F (20°C) 14.4V to 14.8V Self-discharge per month at 68°F (20°C) 1.25% Self-discharge per month at 104°F (40°C) 5% 80% depth of discharge cycles 400

PDF Generated at https://eu.odysseybattery.com 02/17/2023

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODP-AGM35

(35-PC1400)

Battery Type

- Group 35 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12V |
|--|----------------------|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 1200A |
| Cold Cranking Amps (CCA) | 765A |
| HCA | 900A |
| MCA | 770A |
| 20Hr Nominal Capacity (Ah) | 59Ah |
| 10Hr Nominal Capacity (Ah) | 55Ah |
| Reserve Capacity Minutes | 117 mins |
| Terminal | SAE |
| Torque Spec in-lbs (Nm max) | N/A |
| Internal Resistance (m Ω) | $4.3~\text{m}\Omega$ |
| Short Circuit (A) | 1850A |
| | |

Dimensions and Weight

| Length | 9.5 in / 241 mm |
|-----------------------------|--------------------|
| Width | 6.9 in / 175 mm |
| Height (terminals included) | 8.8 in / 224 mm |
| Height (container) | 8.1 in / 206 mm |
| Weight | 50.0 lbs / 22.7 kg |

Temperature

Operating temperature range -40°F/-40°C to 140°F/+60°C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland Tel: +1-800-964-2837

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

