





## **Drawings & Terminal Position**



ODS-AGM16LMJ RIGHT POSITIVE **FEMALE CONNECTION** 





## Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

PDF Generated at https://eu.odysseybattery.com 02/24/2023

Information correct at time of exporting PDF. Please check website for updates.

# **Technical Data Sheet**

ODS-AGM16LMJ

(PC680MJ)

### **Battery Type**

- Group 16 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL) and metal jacket
- Up to 400 cycles at 80% depth of discharge
- Advanced dual purpose battery for engine start and deep

#### **Power and Performance**

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	520A
Cold Cranking Amps (CCA)	170A
HCA	350A
MCA	280A
20Hr Nominal Capacity (Ah)	16Ah
10Hr Nominal Capacity (Ah)	16Ah
Reserve Capacity Minutes	24 mins
Terminal	M6 Receptacle
Torque Spec in-lbs (Nm max)	50 (5.6)
Internal Resistance (m $\Omega$ )	$7~\text{m}\Omega$
Short Circuit (A)	1800A

## **Dimensions and Weight**

Length	7.3 in / 185 mm
Width	3.1 in / 79 mm
Height (terminals included)	6.4 in / 163 mm
Height (container)	6.7 in / 170 mm
Weight	16.6 lbs / 7.5 kg

#### Temperature

Operating temperature range -40°F/-40°C to 176°F/+80°C Optimum storage temperature 68°F/+20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016



**EnerSys World** Headquarters

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

**EnerSys EMEA** EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

