



Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve IUU Charger voltage at 68°F (20°C) 14.4V to 14.8V Self-discharge per month at 68°F (20°C) 1.25% Self-discharge per month at 104°F (40°C) 5% 80% depth of discharge cycles 400

PDF Generated at https://eu.odysseybattery.com 02/24/2023

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODS-AGM28LMJA

(PC925MJT)

Battery Type

- Metal Jacket; Left positive SAE brass posts with 3/8 inch threaded receptacle
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep

Power and Performance

12V
900A
330A
610A
480A
28Ah
27Ah
48 mins
SAE
N/A
$5~\text{m}\Omega$
2400A

Dimensions and Weight

Length	6.6 in / 168 mm
Width	7.1 in / 180 mm
Height (terminals included)	5.8 in / 147 mm
Height (container)	5 in / 127 mm
Weight	25.3 lbs / 11.5 kg

Temperature

Operating temperature range -40°F/-40°C to 176°F/+80°C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road

Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

