




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve IUU

Charger voltage at 68°F (20°C) 14.4V to 14.8V

Self-discharge per month at 68°F (20°C) 1.25%

Self-discharge per month at 104°F (40°C) 5%

80% depth of discharge cycles 400

PDF Generated at https://eu.odysseybattery.com 02/17/2023 11:52:01

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODS-AGM470FTT

(PC1800-FT)

Battery Type

- 3/8 inch threaded front stud terminal
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1800A
Cold Cranking Amps (CCA)	1300A
HCA	1600A
MCA	1450A
20Hr Nominal Capacity (Ah)	214Ah
10Hr Nominal Capacity (Ah)	190Ah
Reserve Capacity Minutes	475 mins
Terminal	3/8-16" Stud
Torque Spec in-lbs (Nm max)	80 (9.0)
Internal Resistance (m Ω)	$3.3~\text{m}\Omega$
Short Circuit (A)	3800A

Dimensions and Weight

Length	22.9 in / 582 mm
Width	4.9 in / 124 mm
Height (terminals included)	12.5 in / 318 mm
Height (container)	12.5 in / 318 mm
Weight	132 lbs / 59.9 kg

Temperature

Operating temperature range $-40^{\circ}\text{F}/-40^{\circ}\text{C}$ to $113^{\circ}\text{F}/+45^{\circ}\text{C}$ Optimum storage temperature $68^{\circ}\text{F}/+20^{\circ}\text{C}$

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA

Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

