




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library



© 2023 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted. Subject to revisions without prior notice. E.&O.E. Date Downloaded: February 24, 2023

PDF Generated at https://eu.odysseybattery.com 02/24/2023 11:53:08

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODS-AGM8E

(PC310)

Battery Type

- Internal threaded tin-plated brass terminals, SS M4 bolts
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
 Advanced dual purpose battery for engine start and deep
- cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	310A
Cold Cranking Amps (CCA)	100A
НСА	200A
MCA	155A
20Hr Nominal Capacity (Ah)	8Ah
10Hr Nominal Capacity (Ah)	7Ah
Reserve Capacity Minutes	9 mins
Terminal	M4 Receptacle
Torque Spec in-lbs (Nm max)	8.9 (1.0)
Internal Resistance (m Ω)	27.1 mΩ
Short Circuit (A)	455A

Dimensions and Weight

5.4 in / 137 mm
3.4 in / 86 mm
3.9 in / 99 mm
3.9 in / 99 mm
5.9 lbs / 2.7 kg

Temperature

Operating temperature range	-40°F/-40°C to 122°F/+50°C
Optimum storage temperature	68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

