




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

PDF Generated at https://eu.odysseybattery.com 02/22/2023

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODX-AGM31M

Battery Type

(31M-PC2150)

- Group 31 with brass SAE posts, 3/8 inch positive and 5/16 inch negative thread SS stud terminals and single external
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	2150A
Cold Cranking Amps (CCA)	1150A
HCA	1545A
MCA	1370A
20Hr Nominal Capacity (Ah)	100Ah
10Hr Nominal Capacity (Ah)	92Ah
Reserve Capacity Minutes	220 mins
Terminal	Μ
Torque Spec in-lbs (Nm max)	200 (22.6)/100 (11.3) studs only
Internal Resistance (m Ω)	$2.2~\text{m}\Omega$
Short Circuit (A)	5000A

Dimensions and Weight

Length	13 in / 330 mm
Width	6.8 in / 173 mm
Height (terminals included)	9.9 in / 251 mm
Height (container)	8.9 in / 226 mm
Weight	77.8 lbs / 35.3 kg

Temperature

Operating temperature range -40°F/-40°C to 176°F/+80°C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 Reading, PA 19605, USA 6300 Zug, Switzerland Tel: +1-800-964-2837

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

